

## Newfoundland Labrador Hydro (NLH)

load shedding (UFLS), is necessary to ensure the integrity and reliability of system equipment. Under frequency events have typically occurred 5 to 8 times per year on the Island Interconnected System and the resultant customer load interruptions are generally less than 30 minutes. With the activation of the Maritime Link frequency controller during the winter of 2018. UFLS events have occurred less frequently.

3. As of 0800 Hours.

Gross output including station service at Holyrood (24.5 MW) and improved NLH hydraulic output due to water levels (35 MW). 4.

- Gross output from all Island sources (including Note 4). 5.
- 6. NLH Island Power Purchases include: CBPP Co-Gen, Nalcor Exploits, Rattle Brook, Star Lake, Wind Generation and capacity assistance (when applicable).
- 7. Adjusted for curtailable load, market activities and the impact of voltage reduction when applicable.
- 8. Due to limitations inherent in the design of combustion turbines, the output of combustion turbines may be reduced in the event that ambient temperatures exceed the threshold

Section 3 Island Peak Demand Information Previous Day Actual Peak and Current Day Forecast Peak			
ri Ann 07 2022			
ri, Apr 07, 2023	Actual Island Peak Demand <sup>9</sup>	10:35	1,441 MW
at, Apr 08, 2023	Forecast Island Peak Demand		1,655 MW